







# PowerMaster Extension FED 3.4






## Technical Data Sheet

Product Code	FED 3.0
Manufacturer's Name	Branach Manufacturing Pty Ltd
Phone Number	+61 3 9761 6633
Certified By (Name, Title)	Pat Driscoll Business Development Manager
Last Updated	5/11/2015

### PROPERTIES

<input checked="" type="checkbox"/> Standards	AS/NZS 1892.3
 Load Rating	160kg
 Electrical Properties	Complies to AS/NZS 1892.3 Section 2.4
 Heat Resistance	130 Degrees Celsius
 Chemical Resistance	Tested to AS/NZS 1892.3
 Accelerated Weathering Test	Tested to AS 2331.3.1
 Warranty	3 years from date of manufacturing

### MEASUREMENTS

 Weight	12.0kg
 Distance Between Rungs	0.305m
 Closed Height	2.40m
 Extended Height	3.40m
 Width	Fly: 0.370m / Base: 0.450m

### COMPONENTS

<b>A</b> Stiles	Fibreglass: ISO-PE resin with e-glass fibres
<b>B</b> Rungs	D-Rung: Aluminium 6060
<b>C</b> Feet	Swivel: 35% GF Nylon
<b>D</b> Rung Wear Strip	HD Polyethylene
<b>E</b> End Caps	35% GF Nylon
<b>F</b> Rope	NA
<b>G</b> Latch	Branach Latch: 316 Stainless steel, coated with PPA
<b>H</b> Ladder Guide Bracket	50mm Alum 6060, e-coat and black powder coat
<b>I</b> Running Guide Bracket	XF 400 Steel zinc plated with gold passivate
<b>J</b> Tie Down Bar	Steel zinc plated with gold passivate
Rivets	Zinc Plated Low Carbon Steel

